

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 26, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2026	TDZXL02.2114	Diesel	Dedicated	Diesel	Variable-speed and Constant-speed

Emission Control Systems	Special Features
[1]: Direct Diesel Injection (DDI), Charge Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Continuous Trap Oxidizer (CTOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kW-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

Applicable Standard		Criteria			Smoke Opacity		
		NMHC+NOx	CO	PM	ACL	LUG	PEAK
Tier 4 Final 37 ≤ kW < 56	STD	4.7	5.0	0.03	*	*	*
	FEL	*	*	*	*	*	*
	NTE	5.9	6.2	0.04	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: That the manufacturer has elected to combine engines from the 19 ≤ kW < 56 power categories into a single engine family. The listed engine models comply with the more stringent set of standards of the 37 ≤ kW < 56 power category in accordance with Section 1039.230(e) of the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 24th day of September 2025.


Robin U. Lang, Chief
Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: TDZXL02.2114 EO Number: U-R-013-0774 Date Applicable: 9/12/25

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	hp	rpm	lb/hr	N-m	rpm	lb/hr	-	-	-
TCD2.2L3	CSEI55E		I3	2.194	74.3	2200	28.5	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSEI55A		I3	2.194	74.3	2600	30.4	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSEI55D		I3	2.194	74.3	2300	29.3	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSEI50A		I3	2.194	67	2600	28	184.3	1600	19.8	1	N/A	
TCD2.2L3	CSEI50D		I3	2.194	67	2300	26.4	184.3	1600	19.8	1	N/A	
TCD2.2L3	CSEI50E		I3	2.194	67	2200	26.1	184.3	1600	19.8	1	N/A	
TCD2.2L3	CSEI45A		I3	2.194	60.3	2600	25.6	184.3	1600	19.8	1	N/A	
TCD2.2L3	CSEI45DL		I3	2.194	60.3	2300	23.4	154.8	1600	17	1	N/A	
TCD2.2L3	CSEI45D		I3	2.194	60.3	2300	23.4	184.3	1600	19.8	1	N/A	
TCD2.2L3	CSEI36A		I3	2.194	48.8	2600	21.6	132.7	1600	14.6	1	N/A	
TCD2.2L3	CSEI36D		I3	2.194	48.8	2300	19.9	132.7	1600	14.6	1	N/A	
TCD2.2L3	CSEI36E		I3	2.194	48.8	2200	19.6	132.7	1600	14.6	1	N/A	
TCD2.2L3	CSET55AT		I3	2.194	74.3	2600	30.4	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSET50AT		I3	2.194	67	2600	28	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSET45AT		I3	2.194	60.3	2600	25.6	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSET55AH		I3	2.194	74.3	2600	30.4	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSET50AH		I3	2.194	67	2600	28	206.5	1600	22.3	1	N/A	
TCD2.2L3	CSET45AH		I3	2.194	60.3	2600	25.6	206.5	1600	22.3	1	N/A	