

Pursuant to the authority vested in the California Air Resources Board by Health and Safety Code Division 026, Part 5, Chapters 1 and 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The engines and emission control systems produced by the manufacturer as described below are certified for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

Model Year	Engine Family	Combustion Cycle	Fuel Operation	Fuel Type(s)	Engine Operation
2026	TDZXL05.7053	Diesel	Dedicated	Diesel	Variable-speed and Constant-speed

Emission Control Systems	Special Features
[1]: Direct Diesel Injection (DDI), Charge Air Cooler (CAC), Exhaust Gas Recirculation (EGR), Electronic Control Module (ECM), Turbocharger (TC), Diesel Oxidation Catalyst (DOC), Continuous Trap Oxidizer (CTOX), Selective Catalytic Reduction – Urea (SCR-U), Ammonia Oxidation Catalyst (AMOX)	None

The certified engine models are attached.

The listed engine models comply with the following: 1) emission standard limits (STD) and Not-To-Exceed (NTE) limits, as applicable, for criteria pollutants non-methane hydrocarbons (NMHC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM), and for smoke opacity as demonstrated during the Acceleration (ACL) and Lugging (LUG) modes, and the peak value (PEAK) in either mode of the Smoke Opacity cycle, as set forth in 13 CCR 2423 and the applicable California test procedures for off-road compression-ignition engines, and 2) family emission limits (FEL) declared by the manufacturer as allowed by the applicable California test procedures, stated in units of gram per kilowatt-hour (g/kW-hr) and percent opacity (%opacity), respectively, except as noted, or designated as not applicable (*).

Applicable Standard		Criteria				Smoke Opacity		
		NMHC	NOx	CO	PM	ACL	LUG	PEAK
Tier 4 Final 75 ≤ kW < 130	STD	0.19	0.40	5.0	0.02	*	*	*
	FEL	*	*	*	*	*	*	*
	NTE	0.28	0.60	6.2	0.03	*	*	*

BE IT FURTHER RESOLVED: Any declared FEL is the emission limit to which all engines must comply in lieu of the standard limit for certification purposes, subject to the restrictions of averaging, banking, or trading (ABT) programs allowed by the applicable California test procedures.

BE IT FURTHER RESOLVED: For the listed engine models, the manufacturer has submitted materials to demonstrate certification compliance with 13 CCR 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models may only be installed in or on equipment such that engine operation is consistent with off-road compression-ignition engines as defined in 13 CCR 2421(a)(39).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed on this 24th day of September 2025.


 Robin U. Lang, Chief
 Emissions Certification and Compliance Division

ATTACHMENT: ENGINE MODELS

Family: TDZXL05.7053 EO Number: U-R-013-0772 Date Applicable: 9/10/25

Model	Code	Trim	Config	Displacement	Peak Power			Peak Torque			ECS Num	GHG	Notes
					Power	Speed	Fueling	Torque	Speed	Fueling			
-	-	-	-	L	hp	rpm	lb/hr	N-m	rpm	mm ³ /stroke	-	-	-
D6J	CFVI129A		I6	5.702	172.9	1800	60.5	850	1350	123	1	N/A	
D6J	CFVI129B		I6	5.702	172.9	1800	60.5	850	1350	123	1	N/A	
D6J	CFVI129C		I6	5.702	172.9	2000	63.9	850	1350	123	1	N/A	
D6J	CFVI115A		I6	5.702	154.2	1900	62.6	716	1400	102.5	1	N/A	
D6J	CFVI129E		I6	5.702	172.9	2000	63.9	850	1350	123	1	N/A	
D6J	CFVI129F		I6	5.702	172.9	2000	63.9	850	1350	123	1	N/A	
D6J	CFVI129G		I6	5.702	172.9	2000	63.9	850	1350	123	1	N/A	
D6J	CFVI129H		I6	5.702	172.9	2000	63.9	850	1350	123	1	N/A	
D6J	CFVI98		I6	5.702	131.4	2200	52.4	820	1400	117.5	1	N/A	
D6J	CFVI115		I6	5.702	154.2	2200	59.7	850	1400	120.5	1	N/A	
SD60F	CFVI115S		I6	5.702	154.2	2200	59.7	850	1400	120.5	1	N/A	
SD60F	CFVI98S		I6	5.702	131.4	2200	52.4	820	1400	117.5	1	N/A	
D6L	CFVI129EU		I6	5.702	172.9	2000	63.9	850	1350	123	1	N/A	
D6L	CFVI129KU		I6	5.702	172.9	1800	60.5	850	1350	123	1	N/A	
D6L	CFVI114HU		I6	5.702	154.2	1900	62.6	716	1400	102.5	1	N/A	
D6L	CFVI114EU		I6	5.702	154.2	2200	59.7	850	1400	120.5	1	N/A	
D6L	CFVI98EU		I6	5.702	131.4	2200	52.4	820	1400	117.5	1	N/A	