

Genuine DEUTZ Oils



Genuine DEUTZ Oils



Genuine DEUTZ Oils

Genuine DEUTZ oils are top class, semi- and fully synthetic operating fluids for highly charged, heavy-duty diesel engines. They are suitable for operation all year round and offer high protection against wear and deposits.

Product features

- ✓ High level of protection against wear and corrosion, even when using diesel fuels with high sulphur content
- ✓ Safe protection against deposits, sludge and sticking
- ✓ Outstanding thermal stability on the basis of low-volatility base oils
- ✓ Extremely low oil and fuel consumption
- ✓ Reduced cold-wear behavior and fast engine permeation
- ✓ Protects the sensitive exhaust after-treatment components, e.g. diesel particulate filter and SCR-catalyst

Product overview

Type	Application	Clearances/ Specifications
TLS 15W40 D	Super high-performance diesel engine oil for supercharged diesel engines.	DEUTZ DQC II-10 ACEA E7 API CI-4
TLX 10W40 FE	Ultra High-Performance Diesel engine oil made from HC-synthesis base oils for highest loads	DEUTZ DQC III-10 ACEA E7/B4/B3/A3 API CI-4 Global DHD-1 JASO DH-1
DQC4 5W30 UHP	Full-synthetic premium-performance engine oil especially for closed crankcase ventilation systems.	DEUTZ DQC IV-10 ACEA E7/E4
Rodon 10W40 Low SAPS	Premium high-performance engine oil for the latest DEUTZ engine generation with exhaust after-treatment.	DEUTZ DQC IV-10 LA ACEA E9/E7/E6 API CI-4 JASO DH-2
Hydraulic and transmission oils	Available upon request	Please specify upon request

Application instructions

- ✓ The feasibility of a lube oil change interval prolongation can be requested at your DEUTZ dealer.
- ✓ Permitted oil service life time can be found in the instruction manuals and in Technical Circular TR 0199-99-1217, depending on the application.
- ✓ The admixture of commercially available additives to genuine DEUTZ engine oils will impair the performance of the oils and is not recommended by DEUTZ.
- ✓ To determine the suitability of DEUTZ engine oils for engines made by other manufacturers, please consult your DEUTZ dealer.
- ✓ Safety datasheets can be obtained from your DEUTZ dealer on request.
- ✓ DEUTZ oils comply with existing regulations of the EU, e.g. 1907/2006 REACH



Technical values typical

		TLS 15W40 D	TLX 10W40 FE	DQC4 5W30 UHP	Rodon 10W40 Low SAPS	
SAE Class		15W40	10W40	5W30	10W40	SAE J 300
TBN	[mg KOH/g]	11,0	10,7	15,4	10,0	DIN ISO 3771
Density	[g/ml]	0,887	0,873	0,860	0,861	DIN 51757
Flash point COC	[°C]	233	236	227	226	DIN ISO 2592
Pourpoint	[°C]	- 36	- 36	- 45	- 33	DIN ISO 3016
Sulfate ash	[Gew. %]	1,39	1,50	1,80	0,94	DIN ISO 51575
Viskosität 40°C	[mm ² /s]	106,9	98,5	72,4	90,0	DIN ISO 51562-1
Viskosität 100°C	[mm ² /s]	14,5	14,8	12,0	13,8	DIN ISO 51562-1
Viskositätsindex (VI)		139	157	164	157	DIN ISO 2909

Genuine DEUTZ Oils

Product portfolio DEUTZ Oils

Type	Part no.	Package size
TLS 15W40 D	0101 6331	5 liters
	0101 6332	20 liters
	0101 6333	209 liters
	0101 6334	Tank wagon
TLX 10W40 FE	0101 6335	5 liters
	0101 6336	20 liters
	0101 6337	209 liters
	0101 6338	Tank wagon
DQC4 5W30 UHP	0101 7849	20 liters
Rodon 10W40 Low SAPS	0101 7976	20 liters
	0101 7977	209 liters



DEUTZ SERVICE
Life Time Support

international:

DEUTZ AG

Ottostr. 1
51149 Köln, Deutschland
Tel. : +49 (0) 221 822-0
Fax : +49 (0) 221 822-3525
E-mail : info@deutz.com
www.deutz.com

DEUTZ (Beijing) Engine Co., Ltd.

1102 CITIC Building
19, Jian Wai Dajie
Beijing 100004, China
Tel. : +86 10 65 25 41 86
Fax : +86 10 65 12 00 42
E-Mail: dbj@deutz.com.cn
www.deutz.com.cn

Deutz Australia Pty. Ltd

Unit 4, 13-15 Brough Street
Springvale, Vic, 3195, Australia
Tel. : +61 3 9549 8400
Fax : +61 3 9549 8490
E-Mail: deutzoz@deutz.com
www.deutz.com.au

DEUTZ Corporation

3883 Steve Reynolds Blvd.
Norcross, GA 30093, USA
Tel. : +1 770 564 7100
Fax : +1 770 564 7222
E-mail : engines@deutzusa.com
www.deutzusa.com

DEUTZ Asia-Pacific (Pte) Ltd.

10 Gul Crescent
Singapore 629523
Tel. : +65 66 72 7800
Fax : +65 62 64 1779 / 62 65 3007
E-mail : dap@deutz.com
www.deutz.com.sg