



DEUTZ SERVICE

OPERATING FLUIDS
Optimal protection
and performance

Whether oils, coolant protection or additives - DEUTZ operating fluids are the perfect solution to keep your engine at peak performance.





DEUTZ Oil

Genuine DEUTZ oils are premium, partly synthetic operating fluids for highly charged and heavily loaded diesel engines. They are suitable for year-round operation, provide high wear protection, and protect against deposits.

Type	Application	Specifications	DEUTZ recommends the use with	Part number	Container Size
Rodon 15W40 D	All-season diesel engine oil for naturally aspirated and turbocharged diesel engines without exhaust aftertreatment	DEUTZ DQC III-18 ACEA E7 API CI-4/SL GLOBAL DHD-1	- DTFR 15B110 (formerly MB 228.3) - CUMMINS CES 20076/7/8 - DETROIT DIESEL 93K215 - MACK EO-N - MTU DDC TYPE 2 - RENAULT RLD/RLD-2 - VOLVO VDS-3	0101 6628 0101 6629 0101 6630 0101 6631	5 Litres 20 Litres 209 Litres Tank truck
TLX 10W40 FE	All-season high-performance diesel engine oil based on MC synthesis base oils for naturally aspirated and turbocharged diesel engines without exhaust after-treatment.	DEUTZ DQC III-18 ACEA E7, A3/B4, API CI-4 GLOBAL DHD-1 JASO DH-1	- DTFR 15B110 (formerly MB 228.3) - MAN M 3275-1 - MTU DDC TYPE 2 - RENAULT RLD/ RLD-2 - VOLVO VDS-3 - VOITH-RETARDER "A"	0101 6335 0101 6336 0101 6337 0101 6338	5 Litres 20 Litres 209 Litres Tank truck
DQC4 5W30 UHP	Ultra high-performance low-friction engine oil for top-performance diesel engines with closed crankcase ventilation and without exhaust aftertreatment.	DEUTZ DQC IV-18 ACEA E7, E4	- DTFR 15B120 (formerly MB 228.5) - MAN M 3277 - MACK EO-N - MTU DDC TYPE 3 - RENAULT RXD/RLD-2 - SCANIA LDF-3 - VOLVO VDS-3 - VOITH-RETARDER "B"	0101 7849	20 Litres
Rodon 10W40 Low SAPS	Premium high-performance low-friction engine oil for the latest DEUTZ engine generation (including TTCD engines) with exhaust aftertreatment, also suitable for DEUTZ CNG, LPG, and gasoline engines.	DEUTZ DQC IV-18 LA ACEA E8, E11, E7 API CI-4 JASO DH-2	- DTFR 15C110 (formerly MB 228.51) - MAN M 3271- 3 - MACK EO-N - MTU DDC TYPE 3.1 - RENAULT RXD/RGD/RLD-2 - VOLVO VDS-3 - KUBOTA without exhaust aftertreatment - YANMAR without exhaust aftertreatment	0101 7976 0101 7977	20 Litres 209 Litres

DEUTZ Coolant

All water-cooled engines require a protective agent to protect the cooling system and maintain long term function. DEUTZ Coolant Core Protect is a perfect match for your DEUTZ engine - for reliable protection all year round.



Type	Application	Specifications	DEUTZ recommends the use with	Part number	Container Size
DEUTZ Coolant Core Protect	Premium performance coolant concentrate based on monoethylene glycol. Nitrite-, amine-, phosphate-, and silicate-free OAT technology.	DQC CB-14 ASTM D3306 ASTM D4985 ASTM D6210 SAE J1034	<ul style="list-style-type: none"> - AGCO Power - IVECO Group FPT FPI9_COOL002 - Ford WSS-M97B44-D - VW TL 774D / VW TL 774F - CNH MAT3624 - John Deere - Komatsu 07.892 (2017) - MB 325.3 - MAN 324 Type SNF - VCS-2A VOLVO Penta / VOLVO Construction / VOLVO Trucks - RENAULT Trucks 41-01-001/-S Type D - MTU MTL 5048 	0101 6694 0101 6695 0101 6696	5 Litres 20 Litres 209 Litres
DEUTZ Coolant Core Protect RM	Premium performance coolant – ready mix based on monoethylene glycol. Nitrite-, amine-, phosphate-, and silicate-free OAT technology. Provides freeze protection down to -36°C / -33°F.	DQC CB-14 ASTM D3306 ASTM D4985 ASTM D6210 SAE J1034	<ul style="list-style-type: none"> - Ford WSS-M97B44-D - VW TL 774F - CNH MAT3624 - John Deere JDM H5 - Komatsu 07.892 (2009) - DAF 74002 - MB 325.3 - MAN 324 Type SNF - VOLVO Penta / VOLVO Construction / VOLVO Trucks 128 6083 / 002 - RENAULT Trucks 41-01-001/-S Type D - MTU MTL 5048 	0101 6697 0101 6698 0101 6699	5 Litres 20 Litres 209 Litres



DEUTZ POWERBLUE

The optimized alternative to conventional urea solution: DEUTZ PowerBlue, with additional additives, uses special active agents to improve the spray pattern of the urea solution into the exhaust stream. This reduces crystallization, and thus equipment downtime and costs. Particularly suitable for low ambient temperatures and applications in low-load operation and with frequent start-stops.

Type	Application	Specifications	DEUTZ recommends the use with	Part number	Container Size
DEUTZ PowerBlue	For all DEUTZ diesel engines with an SCR exhaust aftertreatment system	DIN 70700 ISO 22241-1	For all diesel engines from other manufacturers with an SCR exhaust aftertreatment system	0101 6546 0101 6547 0101 6548	10 Litres 208 Litres 1000 Litres IBC

DEUTZ PREMIUM ADDITIVES



DEUTZ Premium Additives ideally support your diesel engines in meeting a wide range of daily operational demands. DEUTZ FlowBoost is a flow improver that makes summer and transitional diesel usable even at colder temperatures. DEUTZ StartBoost is a powerful fuel additive used to ensure the reliable operation of standby power systems and to significantly slow the aging of diesel fuel. DEUTZ InSyPro Plus, as a 2-in-1 additive, prevents deposits and gumming in sensitive injection components as well as the oxidation of biodiesel content in diesel fuel.

Type	Application	DEUTZ recommends the use with	Part number	Container Size
DEUTZ FlowBoost	Ensuring operational capability by improving cold resistance. Protection of fuel lines and prevention of filter clogging.	For all DEUTZ diesel engines	0109 1260	1 Litres
DEUTZ StartBoost	Increased starting reliability by improving ignition performance (cetane number). Improved fuel storage life through enhanced oxidation and thermal stability, as well as corrosion protection. Protection of the tank, fuel lines, and filters from the occurrence of microorganisms.	For all DEUTZ large engines, as well as power generators and standby power systems.	0109 1262	1 Litres
DEUTZ InSyPro Plus	Improving the storage capability of diesel fuels and preventing deposits in injection systems. Reducing filter contamination and clogging. Ensuring reliable engine starting after extended operating breaks. Normalizing black smoke and reduced engine performance, as well as increased fuel consumption caused by fuel deposits. Specifically recommended for high-pressure injection. Increasing the oxidation stability of biofuel and biofuel content in diesel.	For all DEUTZ diesel engines	0101 6710	1 Litres

We're here for you!
Please contact us.

DEUTZ AG
Ottostrasse 1 · 51149 Cologne, Germany
Phone +49 731 4040 · info@deutz.com

